



On when
it counts.



Application

The 657 Series LED Panel Mount Indicators are designed with a highly durable watertight housing. These indicators are designed for a variety of applications such as:

- Instrument panels
- Gauge
- Dash boards
- Storage compartments
- Control panels
- ...and many more!

Certifications & Ratings

- RoHS compliant
- NEMA 4X IP67

Features & Benefits

- Resist to shock and vibration
- Anti-Capillary Wire
- Fully watertight housing
- Cool-to-the-touch Operation
- Horizontal Viewing Angle - 110°
- Vertical Viewing Angle - 80°
- No light spill
- Non-polarized
- Available in cool white (For other colors, consult factory)

Mechanical Information:

Mounting hole size:	0.687" (17.46 mm)
Max panel thickness:	.350" (8.89 mm)
Mounting torque:	15 in-lbs torque

Electrical Specifications:


Operating voltage:	12 - 32 V DC
Operating temperature:	-31°F to +149°F (-35°C to +65°C)
Storage temperature:	-40°F +212°F (-40°C to +100°C)
Electrical connection:	18AWG wire leads

Construction:

Housing:	Polycarbonate (UL 94V-0)
Lens Material:	Polycarbonate (UL 94V-0)
Termination:	18AWG anti-capillary wire
Lock washer:	Bronze – White Nickel Plated
Nut:	Brass – White Nickel Plated

All values typical unless otherwise stated (tolerance +/- 10%)



657 Series Dimensions


Dimensions are in Inches [mm]

Part Number	Color	Voltage (V DC)	Current (mA)	Typical Intensity (mcd)
657-3009-213F	COOL WHITE	12-32	24	2000
657-3009-803F	GREEN	12-32	24	1960
657-3009-804F	RED	12-32	24	1680
657-3009-806F	BLUE	12-32	24	880

 Dialight reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.dialight.com/Assets/Brochures_And_Catalogs/Illumination/MDEL657CR.pdf

Warranty Statement: EXCEPT FOR THE WARRANTY EXPRESSLY PROVIDED FOR [HEREIN/ABOVE/BELOW], DIALIGHT DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE, AND NONINFRINGEMENT.