

103-00004

HellermannTyton



Article Number: 103-00004

Description: Cable Tie for AT2060, 30lb Tensile Strength, PA66HS, Black, 3000/reel

Base Data	
Local Order Number	T30RA30000HS
Type	T30RA
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs. Available in reels of 3,000 each or bandoliers of 30 each.
Quantity Per	reel
Product Description	Includes AT2060 tool, power supply, power cord, tool cord, and maintenance and operation manual.
Short Description	Cable Tie for AT2060, 30lb Tensile Strength, PA66HS, Black, 3000/reel
Product Dimensions	
Minimum Tensile Strength (Imperial)	30.0lbs
Minimum Tensile Strength (Metric)	135.0N
Length L (Imperial)	6.0"
Length L (Metric)	152.0mm
Cycle Time	1.2 seconds
Identification Plate Position	none
Reel Diameter (Imperial)	17.7"
Reel Diameter (Metric)	450mm
Reel Width (Imperial)	7.197"
Reel Width (Metric)	182.8m
Releasable Closure	No
Voltage Range	27 Volt
Width W (Imperial)	0.14"
Width W (Metric)	3.6mm
Bundle Diameter Min. (Imperial)	0.06"

103-00004



Product Dimensions	Bundle Diameter Min. (Metric)	1.5mm
	Bundle Diameter Max. (Imperial)	1.25"
	Bundle Diameter Max. (Metric)	31.0mm
	Thickness T (Imperial)	0.05"
	Power Supply	Electrical
	Tension Force	Adjustable
	Thickness T (Metric)	1.2mm
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +275°F (-40°C to +135°C)
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	3000
	Package Quantity (Metric)	3000
	Customs Number(Schedule B)	3926909987
	Reel Weight (Imperial)	7lbs
	Reel Weight (Metric)	3.175kg
	Weight (imperial)	3.9lbs