

2.9 mm Male Plug to 2.9 mm Female Jack

Model Number

ADT-2851-MF-29M-02


SPECIFICATIONS

Frequency: DC - 26.5 GHz

VSWR: 1.05 + .005 f (GHz)

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



2.9 mm Female Jack to 2.9 mm Female Jack

Model Number

ADT-2852-FF-29M-02


SPECIFICATIONS

Frequency: DC - 26.5 GHz

VSWR: 1.05 + .005 f (GHz)

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



2.9 mm Male Plug to 2.9 mm Male Plug

Model Number

ADT-2853-MM-29M-02


SPECIFICATIONS

Frequency: DC - 26.5 GHz

VSWR: 1.05 + .005 f (GHz)

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



2.9 mm Female Jack to 2.9 mm Female Jack - Bulkhead Mount

Model Number

ADT-2854-FF-29M-02

SPECIFICATIONS

Frequency: DC - 26.5 GHz

VSWR: 1.05 + .005 f (GHz)

Impedance: 50 Ohms

Finish: Passivated Stainless Steel

