

Article Number: 151-07400

Heavy-Duty Mount, .5" Mounting Hole, 114lb-ft Max Torque, PA66HIRHSUV, Black, 500/pkg Description:

Base Data		
	Local Order Number	HDM500BHIHSUVH4
		HDM500
	Туре	
	Color	Black (BK)
	Features and benefits	 Mount and tie combination makes it easy to service bundles in the field. Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments. Eliminates the needs for multiple sized fix diameter clamps.
	Quantity Per	bag
	Product Description	This heavy duty mount, when used with a cable tie eliminates the need to carry multiple sizes of fixed bundle diameter clamps; which reduces inventory and purchasing costs while simplifying the assembly process.
	Short Description	Heavy-Duty Mount, .5" Mounting Hole, 114lb-ft Max Torque, PA66HIRHSUV, Black, 500/pkg
Product Dimensions		
	Length L (Imperial)	1.9"
	Length L (Metric)	47.0mm
	Fixation Method	Screw Mounting and Rivet
	Width W (Imperial)	1.0"
	Width W (Metric)	25.0mm
	Cable Tie Width Max. (Imperial)	0.5"
	Cable Tie Width Max. (Metric)	12.7mm
	Height H (Imperial)	0.8"
	Height H (Metric)	20.7mm
	Mounting Hole Diameter D (Imperial)	0.5"
	Mounting Hole Diameter D (Metric)	12.95 mm
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat and UV-resistant (PA66HIRHSUV)

generated on: 4/29/2017

151-07400



Material and Specifications	Material Shortcut	PA66HIRHSW
	Flammability	UL 94 HB
	Maximum Torque (kgf-cm)	1576kgf-cm
	Maximum Torque (lbf-ft)	114lbf-ft
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	REACH Compliant (Article 33)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	1kg

generated on: 4/29/2017