

3.5 mm Male Plug to 3.5 mm Female Jack

Model Number

ADT-2733-MF-35M-02


SPECIFICATIONS

Frequency: DC - 26.5 GHz

VSWR: 1.05 + .005 f (GHz)

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



3.5 mm Female Jack to 3.5 mm Female Jack

Model Number

ADT-2735-FF-35M-02


SPECIFICATIONS

Frequency: DC - 26.5 GHz

VSWR: 1.05 + .005 f (GHz)

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



3.5 mm Male Plug to 3.5 mm Male Plug

Model Number

ADT-2734-MM-35M-02


SPECIFICATIONS

Frequency: DC - 26.5 GHz

VSWR: 1.05 + .005 f (GHz)

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



3.5 mm Female Jack to 3.5 mm Female Jack - Bulkhead Mount

Model Number

ADT-2850-FF-35M-02

SPECIFICATIONS

Frequency: DC - 26.5 GHz

VSWR: 1.05 + .005 f (GHz)

Impedance: 50 Ohms

Finish: Passivated Stainless Steel

