

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2006

© COPYRIGHT 2006

Tyco Electronics AMP GmbH

ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
A1	-		B5	ECR-11-013895	29JUN2011	SR	BR
			B6	ECR-11-017365	19AUG2011	SR	BR

Notes

1 SUITABLE CRIMP CONTACTS:
 -SERIES TYPE III+; CUSTOMER DRAWING: 163083
 -SERIES C12; CUSTOMER DRAWING: 927890
 -SERIES HD.M; CUSTOMER DRAWING: 1105001
 -WIRE INSULATION: MAX. \varnothing 4.2 MM
 -DIMENSIONS: (OVER ALL) 21x21x32mm

2 SUITABLE INSERTION TOOL:
 CUSTOMER DRAWING: 1102855-1

3 SUITABLE EXTRACTION TOOL:
 CUSTOMER DRAWING: 1102855-6

4 STANDARDS:
 DIN EN 61984, DIN EN 60664-1

△ 5 AUTHORIZATION; UL: UL-FILE NR.: E101788(R)

6 PACKAGING:
 PN 2-3 10 SETS IN A CARTON, PRE-MOUNTED
 PN 2-4 500 SETS IN A CARTON, PRE-MOUNTED

QTY	DESCRIPTION	MATERIAL	COLOR	ITEM	NOTES
1	FEMALE INSERT	PA66-GF25	LIGHT GREY	6	SERIES HD7, 8-POS., TYPE III+, SIZE1
1	INSULATION COVER	NBR65	BLACK	5	SERIES HD7
1	SCREW THREAD INSERT	BRASS		4	M3x5.5, AFTERMOULD
1	WASHER, SERRATED LOCK	STAINL. STEEL		3	V3.4, DIN 6798 JULY 1988
1	SCREW, SLOTTED COUNTERSUNK FLAT HEAD	STAINL. STEEL		2	M3x6 DIN EN ISO 2009
1	FEMALE INSERT	PC-GF20	LIGHT GREY	1	SERIES HD7, 8-POS., TYPE III+, SIZE1
2-4	DESCRIPTION	MATERIAL	COLOR	ITEM	NOTES

CONTACT ARRANGEMENT
 VIEW FROM TERMINATION SIDE

HD.7.BU.C.250V

HD.7.BU.C.La.250V

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±-
2 PLC	±-
3 PLC	±-
4 PLC	±-
ANGLES	±1°

MATERIAL

-

FINISH

-

DWN 09APR2002

R.SCHNEIDER

CHK 09APR2002

M.SCHWEIGER

APVD 09APR2002

T.SCHNURPFIL

PRODUCT SPEC

108-74002

APPLICATION SPEC

-

WEIGHT

-

CUSTOMER DRAWING

NAME

FEMALE INSERT ASSY
 SERIES HD.7

SIZE

A3

CAGE CODE

00779

DRAWING NO

C=1103001

RESTRICTED TO

-

SCALE 2:1

SHEET 1 OF 1

REV B6

TE Connectivity

1470-19 (3/11)

Pro/ENGINEER DRAWING