



Directive 2002/95/EC
RoHS Compliant

NOTES:

- METALSHIELDS: STEEL; min. 315µm TIN over 40-80µm NICKEL
- INSULATORS: PBT GF UL 94 V-0, BLACK
- CONTACTS: COPPER ALLOY
PLATING: 8µm HARD GOLD over min. 50µm NICKEL
- THREADED SPACER CLIPS:
COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
PCB-HOLE: $\varnothing 3,1 \pm 0,1$; PCB THICKNESS 2,3mm
- COLLARS: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
- MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
- CONNECTOR IS PART MARKED: DSS1XSRAA15X CONEC ABC

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

CUSTOMER APPROVAL DATE:

NAME: TITLE:

COMPANY NAME:

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

finish:				tolerance		dim. in mm	scale: 2:1 (5:1)	
see notes							material: see notes	
DO NOT ALTER CAD DRAWING BY HAND				date	name		title:	
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH				drawn	11.11.09	Sonnenberg	D-SUB FEMALE 9pos. SOLDER PIN STRAIGHT with threaded spacer clip	
				appd.	11.11.09	Koch		
				norm				
				d-old				
a	Origin			CONEC		dwg no: Inventor 10		DIN-A3
rev.	description	date	name			16K1A2573		sh: 1
							part no: DSS1XSRAA15X	