



RESISTANCE @ +25°C = 40 Ω ± 20%
 MAXIMUM STEADY STATE CURRENT = 2 AMPS
 RESISTANCE @ MAXIMUM CURRENT = 0.60 Ω NOMINAL
 DIM "D" = 0.725" MAXIMUM
 DIM "T" = 0.250" MAXIMUM
 DIM "L" = 0.700" MINIMUM
 DIM "S" = 0.310" NOMINAL

LEAD WIRE GAUGE = 18 AWG OR 20 AWG

SEE MANUFACTURING SPECIFICATION (LAYER 1)

"B"	LEAD WIRE GAUGE WAS 20 AWG	07/14/09	DD
"A"	DIM "L" WAS 1" MIN & DIM "D" WAS 0.625" MAX	07/02/09	DD
---	ISO RELEASE	02/05/04	DD
REV	REVISION RECORD	DATE	APP

SCALE	NONE	U.S. SENSOR CORP. 1832 W. COLLINS AVE. ORANGE, CA. 92867 714-639-1000 www.ussensor.com
DRAWN BY	T. SOMERVILLE	
DATE	02/12/90	
REV.	"B"	
LAYER	0 OF 2	
		INRUSH CURRENT LIMITER
		P/N ST40002B