

111-12300



Article Number: 111-12300

Description: Wide-Strap Cable Tie, 9.1" Long, 120lb Tensile Strength, PA66HIRHSUV, Black, 300/pkg

Base Data	Local Order Number	111-12300
	Type	WSS
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> • Wider and thinner strap design increases flexibility, provides low insertion and minimizes pinching of bundles. • Low profile head with clamping rails provide compact bundling with a full circumferential compression around bundles. • Bent tail allows for quick insertion into head or mounts. • High impact, heat and UV stabilized heavy duty cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.
	Quantity Per	bag
	Product Description	The Heavy Duty Wide Strap Cable Tie was designed to minimize the pinching of soft bundles and the potential of lateral movement along the bundle. The low profile head and underside clamping rails increase the grip around the bundle and provide a better fit than traditional cable ties. These are used primarily in the trucking and heavy equipment industries, but can be used in a wide variety of applications where strength is needed.
	Short Description	Wide-Strap Cable Tie, 9.1" Long, 120lb Tensile Strength, PA66HIRHSUV, Black, 300/pkg
Product Dimensions	Minimum Tensile Strength (Imperial)	120.0lbs
	Minimum Tensile Strength (Metric)	535.0N
	Length L (Imperial)	9.1"
	Length L (Metric)	231.0mm
	Fixation Method	None
	Identification Plate Position	none
	Releasable Closure	No
	Tie Closure	plastic pawl
	Variant	Inside Serrated
	Width W (Imperial)	0.5"
	Width W (Metric)	12.7mm

111-12300



Product Dimensions	Bundle Diameter Min. (Imperial)	0.38"
	Bundle Diameter Min. (Metric)	9.7mm
	Bundle Diameter Max. (Imperial)	2.3"
	Bundle Diameter Max. (Metric)	58.4mm
	Thickness T (Imperial)	0.055"
	Cable Tie Head Length (Imperial)	0.393"
	Cable Tie Head Width (Imperial)	0.78"
	Thickness T (Metric)	1.4mm
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Material Shortcut	PA66HIRHSUV
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	300
	Package Quantity (Metric)	300Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	1.8kg