

Distributor - VS-ASI-J-Y-N-SWA-LC - 1433168

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



AS-Interface distributor with IP67 protection for 1 flat-ribbon conductor, 2-pos., with screw connection, angled



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	20.0 GRM
Custom tariff number	85366990
Country of origin	Germany

Technical data

Mechanical characteristics

Number of positions	2
Connection method	AS-i penetration technique
Conductor cross section	0.14 mm ² ... 1 mm ² (solid) 0.14 mm ² ... 0.75 mm ² (With ferrules)
Connection cross section AWG	26 ... 17 (solid) 26 ... 18 (With ferrules)
External cable diameter	6 mm ... 8 mm
Cable exit	angled
Color	black

Ambient conditions

Ambient temperature (operation)	-25 °C ... 70 °C (Plug / socket)
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Degree of protection	IP67

Material data

Distributor - VS-ASI-J-Y-N-SWA-LC - 1433168

Technical data

Material data

Housing material	PA
Contact carrier material	PUR
Contact material	CuZn
Contact surface material	Sn/Au
Sealing material	Neoprene (Flat gasket)
	FPM (O-ring)

Electrical characteristics

Rated voltage (III/3)	32 V
Rated current	≤ 4 A

Classifications

eCl@ss

eCl@ss 4.0	27140815
eCl@ss 4.1	27140815
eCl@ss 5.0	27143423
eCl@ss 5.1	27143423
eCl@ss 6.0	27143423
eCl@ss 7.0	27449001
eCl@ss 8.0	27449001

ETIM

ETIM 2.0	EC000200
ETIM 3.0	EC001856
ETIM 4.0	EC000313
ETIM 5.0	EC000313

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Distributor - VS-ASI-J-Y-N-SWA-LC - 1433168

Approvals

Approvals

GOST

Ex Approvals

Approvals submitted

Approval details



Drawings

Dimensioned drawing

