

Cable gland - G-INB-M20-S68N-NEPDS-S - 1415182

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Cable gland, Cable gland material: Nickel-plated brass, Application: Standard, External cable diameter 6 mm ... 13 mm, Shielding: No, Connecting thread: M20, Color: silver

The figure shows version G-INB-M25-S68N-NEPDS-S



Key Commercial Data

Packing unit	1 STK
Minimum order quantity	5 STK
Weight per Piece (excluding packing)	108.0 g
Custom tariff number	74199990
Country of origin	Germany

Technical data

Dimensions

Length	96 mm
Wrench size, union nut	24 mm
Wrench size, support	24 mm
Hexagon angular dimension GRP	27 mm
Length of the connecting thread	6 mm
Feed-through hole diameter	20.1 mm 20.2 mm
External cable diameter	6 mm 13 mm
	7.5 mm 11.3 mm (For UL 514 B)

Ambient conditions

Degree of protection	IP68 (5 bar / 0.5 h)
	IP69K



Cable gland - G-INB-M20-S68N-NEPDS-S - 1415182


Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C 100 °C (static)
General	
No. of conductors	1
Cable gland material	Nickel-plated brass
Material, insert	PA
Cable seal material	EPDM
O-ring material	EPDM
Shielded	No
Thread type on connection side	M20
Torque	8 Nm (Union nut)
	8 Nm (Support)
Color	silver
Impact category	6
Execution of the strain relief	A

Drawings

Dimensional drawing



Classifications

eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 8.0	27149109
eCl@ss 9.0	27144432

ETIM

ETIM 5.0	EC000441

Flat nut



Cable gland - G-INB-M20-S68N-NEPDS-S - 1415182

Approvals
Approvals
Approvals
UL Recognized / cUL Recognized / GOST-R / cULus Recognized
Ex Approvals
Approvals submitted
Approval details
UL Recognized SU
cUL Recognized 53
GOST-R C
cULus Recognized CSA US
Accessories
Accessories



Cable gland - G-INB-M20-S68N-NEPDS-S - 1415182

Accessories

Nut - A-INL-M20-N-S - 1411242



Nut, Nickel-plated brass, For threads M20, Color: silver

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com