

- Polyamide hand enclosure for automation and control engineering
- Version with handle and integrated cable exit
- Large fitting space

Included in delivery

Enclosure with handle, including cable gland M 20 x 1.5, front panel, enclosure and front panel screws, and wall holder

Technical data Material: polyamide front plate: polystyrol Ingress protection: IP 65 to EN 60529 Impact resistance: 7 Joule to EN 60079-0 Flammability: HB / UL 94 Colour: RAL 1021, rape yellow Temperature range: -40°C to +60°C

Pilot 110 - 150

Programme range


Enclosure type	Order No.	Encl. dimensions incl. handle	Front panel dimensions	Mounting depth
		W x L x H (mm)	W x H (mm)	(mm)
Pilot 110	29.21 10 00	85 x 85 x 191	77 x 77	63,5
Pilot 120	29.21 20 00	115 x 85 x 191	107 x 77	63,5
Pilot 130	29.21 30 00	85 x 85 x 221	77 x 107	63,5
Pilot 140	29.21 40 00	160 x 85 x 211	152 x 97	63,5
Pilot 150	29.21 50 00	105 x 85 x 266	97 x 152	63,5

Accessories

Magnetic holder (for Pilot 120 - 150)	29.00 00 80
Push button and switches see page 53 - 58	on request



Electromechanical components On request, we can supply equipment fitted with electro-mechanical components such as emergency stop button, acknowledge keys, hand wheel, switches, display



Wall holder included in delivery


Dimensions





Туре	Order No.	Weight (kg)	
Pilot 110	29.21 10 00	0.500	
85 78/77.5	70.5/68 6.65 55/53	85 78/77.5 70.5/68 65 55/53	85 80 63.5




Туре	Order No.	Weight (kg)
Pilot 120	29.21 20 00	0.500
Pilot 130	29.21 30 00	0.500










Pilot 110 - 150

Dimensions



Accessories



Magnetic holder for Pilot 120 - 150, self-adhesive dimensions: 90 x 30 x 7.5 mm

Order No. 29. 00 00 80