HellermannTyton

Heavy-Duty Mount, .3125" Mounting Hole, 114lb-ft Max

Torque, PA66HIRHSUV, Black, 100/pkg



Article Number: 151-00444

Description:

Base Data Local Order Number HDM320BHIHSUVC2 HDM320 Type Color Black (BK) Features and Benefits · Mount and tie combination makes it easy to service bundles in the field. · Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments. · Eliminates the needs for multiple sized fix diameter clamps. Quantity Per bag **Product Description** This heavy duty mount, when used with a cable tie eliminates the need to carry multiple sizes of fixed bundle diameter clamps; which reduces inventory and purchasing costs while simplifying the assembly process. Short Description Heavy-Duty Mount, .3125" Mounting Hole, 114lb-ft Max Torque, PA66HIRHSUV, Black, 100/pkg Product Dimensions Length L (Imperial) 1.9" Length L (Metric) 47.0mm **Fixation Method** Screw Mounting and Rivet Width W (Imperial) 1.0" Width W (Metric) 25.0mm Cable Tie Width Max. (Imperial) 0.5" Cable Tie Width Max. (Metric) 12.7mm Height H (Imperial) 0.8" Height H (Metric) 20.7mm Mounting Hole Diameter D (Imperial) 0.4" Mounting Hole Diameter D (Metric) 8.31 mm Material and Specifications Material Polyamide 6.6 high impact modified, heat and UV-resistant (PA66HIRHSUV)

151-00444

HellermannTyton

Material and Specifications	Material Shortcut	PA66HIRHSUV
	Flammability	UL 94 V2
	Maximum Torque (kgf-cm)	1576kgf-cm
	Maximum Torque (lbf-ft)	114lbf-ft
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	19.3kg